

XGA 短焦投影機

# Vivitek DX881ST

XGA 短焦高亮度投影機



## Features

- 超高亮度3300流明及15000:1超高對比
- 短距離大畫面1公尺可投射約80吋大畫面
- DLP® and BrilliantColor™ technologies from Texas Instruments
- XGA (1024 x 768) resolution with a maximum resolution up to WUXGA (1920x1200)
- 多種不同類型影音訊號輸入及輸出 (HDMI, VGA, S-Video, Composite Video, Audio-In/Out)
- 3D相容支援DLP® Link™ 及 HDMI 1.4技術支援 (藍光格式)
- 6階(RYGCWB)色輪鮮豔色彩呈現
- 密閉式光機
- 內建雙10W

## 規格

顯示技術	DLP
亮度	3,300 流明
真實解析度	XGA (1024 x 768)
最大解析度	WUXGA (1920x1200)@60Hz
對比度	15,000:1
燈泡	3500/5000 Hours (Normal/Eco.Mode), 240W/190W
投射比	0.62 (100cm@80")
影像尺寸(對角線)*	60" - 100"
投射距離*	0.76m ~ 1.27m (2.49ft ~ 4.17ft)
鏡頭*	F2.8, f=7.26mm @ 77 inch
變焦*	Fixed
影像比例	4:3 Native
仰角	116.2% +/- 10%
梯形修正	+/- 40 Degree; +/- 40 Steps
Horizontal Frequency	15, 31 - 91Hz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
鏡頭位移	N/A
3D支援	Yes (DLP® Link™, HDMI 1.4b (Blu-Ray))
喇叭	10W x 2 (Mono)
影像規格	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
輸入及輸出	HDMI v1.4b, VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack)(x3), VGA-Out, USB (Type A for power only), Audio-Out (Mini-Jack), RJ45, RS-232C, Mini-USB (Service), Microphone (Mini-Jack), 12V Trigger
吊掛方式	Table Top, Ceiling Mount (Front or Rear)
安全鎖	Kensington® Security Slot, Security Bar, Keypad Lock
體積 (WxDxH)	319 x 205 x 96mm (12.5" x 8.1" x 3.7")
重量	3.17kg (7lbs)
顏色	Two Tone Color (White /Gray)
噪聲值	36dB/32dB (Normal/Eco. Mode)
電源	AC 110-240V, 50/60Hz
耗能	280W (Eco. Mode), 330W (Normal Mode), <0.5W (Standby Mode), <6W (LAN Standby Mode)
標準配件	AC Power Cord, VGA Cable, Remote Control, Lens Cap, Documentation Kit
選購配件	Replacement Lamp

©2014 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.



## 產品圖

