

多媒體投影機

Vivitek DW868

高亮度 WXGA 投影機



特色

- 4500 流明高亮度投影機 15,000:1 高對比
- DLP® and BrilliantColor™ 德州儀器影像處理技術
- WXGA (1280 x 800) 解析度,最高可支援到 UXGA (1600 x 1200)
- 3D compatibility with DLP® Link™ for dazzling and realistic life-like images
- 多種不同輸影像輸入介面: HDMI 1.4b1, DisplayPort, VGA-in (2x), VGA-Out, composite video, component video, S-video
- 高壽命燈泡高達 7,000 小時 (動態節能模式)
- 高輸出 10W 喇叭
- RJ45網路管理連結
- Crestron® RoomView™ 網路管理功能

規格

顯示技術	Single 0.65" DLP Technology by TI
亮度	4,500 流明
真實解析度	WXGA (1280 x 800)
最大解析度	Up to UXGA (1600 x 1200)@60Hz
對比度	15,000:1
燈泡	3000/4000/7000 Hours (Normal/Eco.Mode/ Dynamic Eco Mode),280W/230W
投射比	1.54 - 1.7:1
影像尺寸(對角線)*	27.1" - 302.2"
投射距離*	1 - 10m (3.28ft to 32.8ft)
鏡頭*	F#2.52~2.72, f=21.8-24mm
變焦*	1.1x
影像比例	16:10
仰角	115.5% (JIS)/123% +/- 10%
梯形修正	; +/- 40 步階
Horizontal Frequency	15, 30 - 91.4Hz
Vertical Scan Rate	43 - 87Hz
鏡頭位移	N/A
3D支援	Yes (DLP® Link™)
喇叭	10W
影像規格	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
輸入及輸出	HDMI v1.4b, VGA-In (x2), DisplayPort, Composite Video, S-Video, Audio-In RCA (L/R), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ45, 12V Trigger, RS-232C, USB Mini-B (Service)
吊掛方式	Table Top, Ceiling Mount (Front or Rear)
安全鎖	Kensington® Security Slot, Security Bar, Keypad Lock
體積 (WxDxH)	285 x 261 x 121.8mm (11.22" x 10.3" x 4.8")
重量	3.15kg (6.94lbs)
顏色	White
噪聲值	39dB/37dB (Normal/Eco. Mode)
電源	AC 110-240V, 50/60Hz
耗能	290W (Eco. Mode), 340W (Normal Mode), <0.5W (Standby Mode)
標準配件	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Lens Cap, Documentation Kit
選購配件	Replacement Lamp, Remote, Carrying Case

©2014 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

產品圖

