

多媒體投影機

# Vivitek D867

XGA 多媒體投影機



## 特色

- 真實XGA(1024 x 768)解析度最大支援UXGA (1600 x 1200)
- 超高4000流明亮度及5000:1高對比度畫質
- DLP<sup>®</sup> and BrilliantColor™ 技術讓影像更為細緻
- 多樣的輸入介面HDMI 1.4及Display port高畫質
- 快速上蓋更換燈泡設計
- 內建10W喇叭
- 封閉式光機，灰塵不會影響畫質及投影品質
- RJ 45網路控制介面
- 

## Photos



## 規格

投影技術	Single 0.55" DLP <sup>®</sup> Technology by TI
亮度	4000 ANSI Lumens
解析度	XGA (1024 x 768)
支援最大解析度	Up to UXGA 1600x1200@60 Hz
對比度	5,000:1
燈泡壽命	3000/4000 Hours (Normal/Eco Mode), 280W/245W
投射比	1.6 - 1.92 : 1
螢幕尺寸(對角線)	25.6"-308"
投射距離	1 - 10 m (3.28ft to 32.8ft)
鏡頭	F=2.50~2.72, f = 17.81~22.35mm
變焦	1.2x
影像比例	4:3
仰角	128% +/-10%
梯型修正	Vertical +/- 40° , +/- 40 Step
Horizontal Frequency	15, 30 – 91.4kHz
Vertical Frequency	43 - 87Hz
3D 功能	Yes (Via DLP <sup>®</sup> Link™, BluRay 3D)
喇叭	10W (Mono)
影像訊號	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
輸入及輸出	VGA-In (x2), HDMI v.1.4, DisplayPort, S-Video, Composite, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ45, 12V-Trigger, RS-232, Mini-USB (Service)
吊掛方式	Table Top, Ceiling Mount (Front or Rear)
安全鎖	Kensington <sup>®</sup> Security Slot, Security Bar
體積(W x D x H)	285 x 261 x 121.8 mm (11.22" x 10.3" x 4.8")
重量	3.15kgs (6.94 lbs)
顏色	39dB/37dB (Normal/Eco Mode)
噪聲	White
供電	AC 100-240V, 50/60Hz
耗電	350W (Normal Mode), 300W (Eco. Mode), <0.5W (Standby Mode)
標準配件	AC Power Cord, VGA Cable, Remote Control, Carry Case, Lens Cap, Documentation Kit
選購配件	Replacement Lamp, Remote Control, Carry Case

©2013 Vivitek Corporation. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

