

高亮度 Full HD 投影機

# Vivitek DH976-WT

High performance, high brightness 1080p multimedia projector



## Features

- 高解析度 Full HD 1080p (1920x1080) 以及 4,800 流明高亮度, 15,000:1 超高對比度
- 白色外觀
- 多樣化的影像輸入及輸出 (HDMI 1.4b, DisplayPort, VGA, S-Video, Composite Video), 控制輸入 (RJ45, USB, RS232, 12v trigger) 以及音源 (audio-in/out)

## 產品圖



## 規格

顯示技術	Single 0.65" DLP 德州儀器
亮度	4,800 流明
解析度	1080P (1920 x 1080)
支援最大解析度	WUXGA (1920x1200)@60Hz
對比度	15,000:1
燈泡壽命/類型	2500/3500/4000 Hours (Normal /Eco/Dynamic Eco Mode) 310W/245W
投射比	1.39 - 2.09
影像尺寸 (對角線)	25.9" - 324.9"
投影距離	1.2m - 10m (3.97' to 32.8')
鏡頭	F/#2.42 - 2.97, f=20.9 - 31.05
變焦	1.5x
畫面比例	16:9 Native
仰角	111% ±5% ~ 131% ±5%
梯形修正	Vertical ±30°
水平頻率	15, 31 - 91Hz
垂直頻率	24 - 30Hz, 47 - 120Hz
鏡頭位移	Yes (Vertical/Manual)
3D 支援	Yes (DLP® Link™, HDMI 1.4b (Blu-Ray))
揚聲器	3W (Mono)
電腦訊號支援	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac
影像格式支援	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
輸入及輸出	VGA-In (x2), HDMI v1.4 (x2), DisplayPort, S-Video, Composite Video, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ45, 12V-Trigger, RS-232, 3D-Sync-Out, Mini-USB (Service)
投影方式	Table Top, Ceiling Mount (Front or Rear)
安全鎖	Kensington® Security Slot, Security Bar, Keypad Lock
體積 (WxDxH)	332.8 x 255 x 114.6mm (13.1" x 10" x 4.5")
重量	3.95kg (8.7lbs)
顏色	白
噪聲值	36dB/30dB (Normal/Eco. Mode)
電源	AC 110-240V, 50/60Hz
耗能	370W (Normal Mode), 300W (Eco. Mode), <0.5W (Standby Mode), <6W (LAN Standby Mode)
標準配件	電源線, VGA 傳輸線, 遙控器, 鏡頭蓋, 攜行包, 隨附文件
選購配件	燈泡, 濾網

©2015 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

