

家用劇院投影機

Vivitek H1188

高解析度家用劇院投影機



特色

- 高解析度 1080p (1920x1080) 高品質影像技術
- 高亮度 2,000 流明 及 50,000:1 超高對比度
- DLP® DarkChip3™ and BrilliantColor™ 影像處理技術
- 支援3D影像訊號(DLP link/藍光3D)
- 2D轉3D影像訊號
- 支援 MHL 智慧裝置影像訊號輸入
- 內建10W揚聲器

規格

顯示技術	Single 0.65" DLP® Technology by TI
亮度	2,000 流明
解析度	1080P (1920 x 1080)
支援最大解析度	WUXGA (1920 x 1200) @60Hz
對比度	50,000:1
燈泡壽命	3,000/4,000/5,000 小時(Normal/Eco./Dynamic Eco. Mode) 260/205W
投射比	1.39 - 2.09:1
螢幕尺寸 (對角線)	25.9" - 324.9"
投影距離	1.2m - 10m (3.936ft to 32.8ft)
鏡頭	F=2.418-2.97, f=20.7-31.05mm
變焦	1.5x
螢幕比例	16:9
仰角	130% ±10%
梯形修正	±40 Degree; ±40 Steps
水平頻率	15, 31 ~ 91.4kHz
垂直頻率	24 ~ 30Hz, 47 ~ 120Hz
3D 支援	Yes (Via DLP® Link™, Blu-ray 3D)
揚聲器	10W (Mono)
支援電腦訊號	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac
支援影像訊號	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
輸入及輸出	HDMI v1.4, MHL/HDMI v1.4, VGA-In, Component (YPbPr RCA x 3), Composite Video, Audio-In (RCA), 12V-Trigger (Mini-Jack), RS-232C, 3D-Sync-Out, USB Power (5V, 1.5A), Mini-USB (Service)
吊掛方式	Table Top, Ceiling Mount (Front or Rear)
安全鎖	Kensington® Security Slot, Security Bar
體積 (W x D x H)	286.3 x 272.2 x 128.1mm (11.2" x 10.7" x 5")
重量	3.48kg (7.67lbs)
顏色	黑色
噪聲值	34dB/29dB (Normal/Eco Mode)
電源	AC 100-240V, 50/60Hz
耗能	310W (Normal Mode), 250W (Eco. Mode), <0.5W (Standby Mode)
標準配件	電源線, HDMI 訊號傳輸線, 遙控器, 攜行袋, 鏡頭蓋, 隨附文件
選購配件	燈泡, 濾網

©2015 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

產品圖

