

家用劇院投影機

Vivitek H1186

Full HD 1080p 高影像品質投影



特色

- 2,000 流明亮度以及 50,000:1 超高影像對比度
- Full HD 1080p (1920 x 1080) 解析度,最大可支援至 WUXGA(1920 x 1200)
- DLP® DarkChip3™ and BrilliantColor™ 德州儀器第三代影像處理晶片,能夠提供更高水準的影像品質
- 6 階色輪(RGBRGB)提供更加色彩豔麗畫質
- 多樣化的訊號輸入 HDMI v1.4, VGA-in, S-video, component 及 composite
- 垂直鏡頭位移使安裝調整更為方便
- 動態 3D SRS WOW® 揚聲技術並內建 10W 揚聲器
- Crestron® RoomView™ 系統控制相容

Photos



規格

顯示技術	Single 0.65" DLP® 德州儀器技術
亮度	2,000 流明
解析度	1080P (1920 x 1080)
支援最大解析度	WUXGA (1920 x 1200) @60Hz
對比度	50,000:1
燈泡壽命/類型	3,500/5,000/7,000 (Normal/Eco/Dynamic Eco. Mode) 240/190W
投射比	1.39 - 2.09:1
投影尺寸 (對比度)	25.9" - 324.9"
投影距離	1.2m - 10m (3.936ft to 32.8ft)
鏡頭	F=2.418-2.97, f=20.7-31.05mm
變焦	1.5x
投影比例	16:9
仰角	130% ±10%
梯形修正	±40 度; ±40 步階
水平頻率	15, 31 ~ 91.4kHz
垂直頻率	24 ~ 30Hz, 47 ~ 120Hz
3D 支援	Yes (Via DLP® Link™, Blu-ray 3D)
揚聲器	10W (Mono) with SRS WOW® Dynamic 3D Audio
支援解析度	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA @60hz, Mac
支援影像訊號	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
輸入及輸出	HDMI v1.4, MHL/HDMI v1.4, VGA-In, Component (YPbPr RCA x 3), S-Video, Composite Video, Audio-In (RCA L/R), Audio-In (Mini-Jack), Audio-Out (Mini-Jack), 12V-Trigger (Mini-Jack), RS-232C, 3D-Sync-Out, USB Power (5V, 1.5A), Mini-USB (Service)
吊掛方式	Table Top, Ceiling Mount (Front or Rear)
安全鎖	Kensington® Security Slot, Security Bar, Keypad Lock
體積 (W x D x H)	286.3 x 272.2 x 128.1mm (11.2" x 10.7" x 5")
重量	3.37kg (7.43lbs)
顏色	白
噪聲值	33dB/29dB (Normal/Eco Mode)
電源	AC 100-240V, 50/60Hz
耗能	310W (Normal Mode), 250W (Eco. Mode), <0.5W (Standby Mode)
標準配件	電源線, HDMI 線, 遙控器, 攜行包, 鏡頭蓋, 隨附文件
選購配件	燈泡, 空氣濾網

©2015 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

