

Large Venue Projector

# Vivitek D5380U

WUXGA High Brightness Installation Projector



## Features

- WUXGA 高解析度
- 5000 流明高亮度及2000:1高對比
- DLP® and BrilliantColor™ 投影技術
- 置中鏡頭簡易安裝
- 水平及垂直鏡頭位移
- 多輸入介面: HDMI v1.4, DisplayPort, VGA-Out, RJ45 and RS-232C

## Photos



## 規格

投影技術	Single 0.67" DLP Technology by TI
亮度	5000 流明
真實解析度	WUXGA (1920x1200)
支援解析度	WUXGA (1920x1200) @60Hz
對比度	2,000:1
燈泡壽命	1500/3500 hours (Normal/Eco Mode) 370W / 280W
投射比*	1.54 - 1.93 : 1
影像尺寸 (對角線)*	36"~211"
投射距離*	1.5 - 7 m (4.92ft to 23ft)
鏡頭*	F = 2.46 - 2.56 f = 22.82 - 28.49 mm
變焦*	1.25x
影像比例	16:10
鏡頭位移	Manual Lens Shift
梯形修正	Vertical +/- 40°
Horizontal Frequency	15, 31 – 91.4kHz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
3D Ready	Yes (Supports DLP Link, Blu-Ray 3D)
揚聲器	3W x 2 (Stereo)
鏡頭位移	Vertical -15%/+55%, Horizontal +/-5%
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
輸入/輸出訊號	HDMI v1.4b, DisplayPort, DVI-D, Component (5 BNC) (RGBHV), Component (YPbPr –RCA x3), VGA-In (x2), S-Video, Composite Video, Audio-In RCA (L/R)(x2), Audio-In (Mini-Jack)(x2), VGA-Out, Audio-Out (Mini-Jack), RJ45, 12V Trigger, 3D Sync-Out, RS-232C, USB Power (5V, 1.5A), USB (Service), Remote Jack (Wire Remote)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
安全鎖	Kensington® Security Slot, Security Bar, Keypad Lock
體積(W x D x H)	431 x 344 x 180mm (17"x 13.5" x 7.1")
重量	8.6 kg (19 lbs)
噪聲	42dB/37dB (Normal/Eco Mode)
電源	AC 100-240V, 50/60Hz
耗電	450W (Normal Mode), 340W (Eco. Mode), <0.5W (Standby Mode)
標準配件	AC Power Cord, VGA Cable, Remote Control, Lens Cover, Documentation Kit
選購配件	Replacement Lamp, Remote Control, 3 Interchangeable Lens Options

\*Note: Standard Lens

## 選購鏡頭

Lens	短焦	標準	長焦
投射比	0.77	1.54~1.93	1.93~2.89
變焦	N/A	1.25	1.5
F	11.5	22.8 ~ 28.5	28.5~42.75
F#	2.5	2.46~2.56	2.5~3.1
螢幕尺寸	30.2-181"	36.1~210"	32.1~481"
投射距離	0.5- 3.0m	1.5-7m	2.0-20m

©2013 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

